

## ISDB-T HD Receiver



General	
Model Name	WIT409
Marketing Area	Brazil
Power Voltage	100-250V,50Hz
Power Consumption	10W
Standby power consumption	<2W No
Transponder	ISDB-T

System	
Main Processor	MSTAR7828L
DDR	DDR2 2X512M B
FLASH Size	Flash 32MB

Video Decoder	
Composite	1.0+-0.2Vp-p
Load impedance	75Ω
Max Resolution	1080i(HDMI output)
RGB	700+-140mV p-p,75Ω

**Audio Decoder**

Analogue	2.0+-1.0Vrms
Digital	0.5+-0.1 Vp-p(Coxial)
Max sampling rate	24bit/192KHz
Frequency Response	20Hz-20KHz(at 1KHz 0dB)
Signal noise Ratio	>=90dB
Distortion	<=-60dB
Channel Separation 1KHz	>=80dB(Mixed output)
Dynamic Range	>=80dB

**Front Panel**

Display Type	2 Color LED
LED display	Optional
Front panel keyboard	Optional
Power indicator(LED)	Yes

**Terminal**

ISDB RF antenna input	Yes
RCA	Yes
Coxial Output	Yes
YPbPr	Yes
S-Video	Yes
USB output	Yes
HDMI 1.3	Yes

**Acessory**

Remote control with battery	Yes
AV cable	Optional
S-Video cable	Optional
User's Manual	Yes
Warranty Card	Optional

**Features**

OSD language	Multi-Language
EGP	Yes
subtitle	Yes
Teletext	VBI/OSD
Timer setting manual	Yes
Easy First Installation	Yes
TV and Radio list handling	Yes
Favorite list editing for both radio and TV	Yes
Channel search with automatic/manual scan	Yes
Parental lock by PIN code	Yes
Aspect ratio handling	Yes
LCN	Yes
OTG	Optional
Media Palyback(MP3,WMA,JPEG)	Yes
Game	Optional
Software update by USB	Yes
PVR	Optional
Close Caption	Optional

**Dimensions**

Body size	W248*D153*H38mm
Packing size	W280*D225*H50mm
Net weight	