

X-MICRO TV-Bar



Features:

- Digital terrestrial TV receiving and Radio program receiving
- Scalable video window, up to full screen display.
- COFDM demodulation supports ISDB protocol ETSI (ETS 300 744)
- Supports SDTV and HDTV broadcasts.
- Supports Microsoft DXA (Direct X Acceleration) for HDTV reception.
- Teletext & EPG supported.
- Real-time MPEG2 recording for ISDB-T program.
- Schedule Recording and one-touch recording from EPG.
- Still image snapshots of live video.
- Time Shifting function to pause, rewind, and fast forward live TV.
- Microsoft MCE supported.
- Remote controller
- Compliant with USB2.0 Spec

Specification:

Description	Features
Product Name	X-Micro TV BAR ISDB-T
Model Name	XDVB-TCU
DVBT tuner	<ul style="list-style-type: none"> • Digital terrestrial TV receiving and Radio program receiving. • Bandwidth setting 6M/7M/8M for worldwide DVB-T broadcasting. • COFDM demodulation supports DVB-T protocol ETSI specification (ETS 300 744)
Interface	USB2.0 High speed 480Mbps
I/O	One RF connector for ISDB-T input
Power	Supplied by USB bus
Power voltage (DC)	+5V ; +/- 10%
Power Consumption	500ma@5V
Driver	Microsoft BDA driver structure. Microsoft MCE supported.
RF (DVB-T)	RF input; Coaxial connector impedance 75 ohm
Environment Temperature	Operation: 0~45 ° ; Storage: -10~60 °
Environment Humidity	Operation: 0~90% RH Storage: 0~90% RH
Dimension	95 x 25 x 13 mm

Accessories:

TV in dongle (RF cable)	Total length = 196mm +/-5mm Impedance 75 ohm	
Antenna	Band	VHF and UHF
	Total height	335mm+/-5mm
	Length	1260mm +/-10mm
Remote controller	48mm*80mm*9mm, 17 keys	